

Technische Daten Tianli AG RS

Tyre Size	Load Speed Index	TT/TL	TRA	Tread Depth	Rim	Outer Diameter	Section Width	Inflation Pressure	Load Capacity	Speed
				mm		mm	mm	KPa	Kg	Km/h
380/85R26	127A8/127 B	TL	R-1	38.0	12.00	1295	378	160	1750	50
620/75R26	166A8/166 B	TL	R-1	45.0	20.00	1605	641	320	5300	50
750/65R26	158A8/158 B	TL	R-1	46.0	25.00	1600	761	160	4250	50
	166A8/166 B	TL						240	5300	50
	172A8/172 B	TL						320	6300	50
420/85R28	139A8/139 B	TL	R-1	39.0	15.00	1403	448	160	2430	50
380/85R30	135A8/135 B	TL	R-1	38.0	12.00	1407	380	160	2180	50
650/75R32	172A8/172 B	TL	R-1	48.0	20.00	1796	658	320	6300	50
*650/75R32	180A8/180 B	TL	R-1	48.0	20.00	1796	658	500	8000	50
*IF1050/50 R32	185B/185D	TL	R-1	40.0	36.00	1863	1038	240	9250	50
420/80R46	151A8/151 B	TL	R-1	40.0	13.00	1848	398	240	3450	50
320/90R50	150A8/150 B	TL	R-1	36.0	10.00	1828	305	360	3350	50

*:With Steel Belt