

## Technische Daten

## Tianli AG-RADIAL

Tyre Size	Load Speed Index	TT/TL	TRA	Tread Depth	Rim	Outer Diameter	Section Width	Inflation Pressure	Load Capacity	Speed
				mm		mm	mm	KPa	Kg	Km/h
280/85R20	112A8/112B	TL	R-1W	42.0	10.00	986	282	160	1120	50
280/85R24	115A8/115B	TL	R-1W	42.0	10.00	1080	285	160	1215	50
320/85R24	122A8/122B	TL	R-1W	43.0	11.00	1139	322	160	1500	50
340/85R24	125A8/125B	TL	R-1W	45.0	12.00	1191	353	160	1650	50
380/85R24	131A8/131B	TL	R-1W	47.0	12.00	1273	382	160	1950	50
420/85R24	137A8/137B	TL	R-1W	48.0	15.00	1322	439	160	2300	50
280/85R28	118A8/118B	TL	R-1W	42.0	10.00	1182	283	160	1320	50
320/85R28	124A8/124B	TL	R-1W	43.0	11.00	1258	321	160	1600	50
340/85R28	127A8/127B	TL	R-1W	45.0	12.00	1308	353	160	1750	50
380/85R28	133A8/133B	TL	R-1W	47.0	13.00	1378	386	160	2060	50
420/85R28	139A8/139B	TL	R-1W	48.0	15.00	1438	439	160	2430	50
380/85R30	135A8/135B	TL	R-1W	46.0	13.00	1407	388	160	2180	50
420/85R30	140A8/140B	TL	R-1W	48.0	15.00	1483	439	160	2500	50
420/90R30	142A8/142B	TL	R-1W	48.0	13.00	1496	434	160	2650	50
	147A8/147B	TL						240	3075	50
460/85R30	145A8/145B	TL	R-1W	50.0	16.00	1527	466	160	2900	50
380/85R34	137A8/137B	TL	R-1W	46.0	12.00	1487	389	160	2300	50
420/85R34	142A8/142B	TL	R-1W	48.0	15.00	1594	439	160	2650	50
460/85R34	147A8/147B	TL	R-1W	50.0	16.00	1649	470	160	3075	50
	157A8/157B	TL						320	4125	50
320/85R38	129A8/129B	TL	R-1W	43.0	11.00	1496	310	160	1850	50
380/80R38	142A8/142B	TL	R-1W	46.0	12.00	1595	377	240	2650	50
420/85R38	144A8/144B	TL	R-1W	48.0	15.00	1667	439	160	2800	50
460/85R38	149A8/149B	TL	R-1W	50.0	16.00	1737	470	160	3250	50
	151A8/151B	TL						200	3450	50
520/85R38	155A8/155B	TL	R-1W	51.0	18.00	1863	530	160	3875	50
	175A8/175B	TL						360	6900	50
650/85R38	173D/176A8	TL	R-1W	60.0	20.00	2072	666	240	7100	50
460/85R42	151A8/151B	TL	R-1W	50.0	16.00	1865	473	160	3450	50
520/85R42	157A8/157B	TL	R-1W	51.0	18.00	1958	530	160	4125	50
	162A8/162B	TL						240	4750	50

	165A8/165B	TL						360	5150	50
380/90R46	149A8/149B	TL	R-1W	47.0	12.00	1868	391	240	3250	50
	159A8/159B	TL						400	4375	50
VF380/90R46	173B/173D	TL	R-1W	47.0	13.00	1868	395	440	6500	50
480/80R46	158A8/158B	TL	R-1W	49.0	16.00	1971	490	240	4250	50
520/85R46	158A8/158B	TL	R-1W	51.0	18.00	2062	535	160	4250	50
360/70R24	122A8/122B	TL	R-1W	42.0	11.00	1135	354	160	1500	50
380/70R24	125A8/125B	TL	R-1W	42.0	12.00	1198	384	160	1650	50
420/70R24	130A8/130B	TL	R-1W	45.0	13.00	1231	426	160	1900	50
480/70R24	138A8/138B	TL	R-1W	47.0	15.00	1314	488	160	2360	50
360/70R28	125A8/125B	TL	R-1W	42.0	11.00	1258	356	160	1650	50
380/70R28	127A8/127B	TL	R-1W	42.0	12.00	1304	382	160	1750	50
420/70R28	133A8/133B	TL	R-1W	45.0	13.00	1350	414	160	2060	50
480/70R28	140A8/140B	TL	R-1W	47.0	15.00	1431	477	160	2500	50
420/70R30	134A8/134B	TL	R-1W	45.0	13.00	1384	422	160	2120	50
480/70R30	141A8/141B	TL	R-1W	47.0	15.00	1463	480	160	2575	50
520/70R30	151A8/151B	TL	R-1W	48.0	16.00	1528	522	240	3450	50
600/70R30	152A8/152B	TL	R-1W	51.0	20.00	1610	586	160	3550	50
480/70R34	143A8/143B	TL	R-1W	47.0	15.00	1571	487	160	2725	50
520/70R34	148A8/148B	TL	R-1W	48.0	16.00	1639	530	160	3150	50
600/70R34	160D/163A8	TL	R-1W	51.0	20.00	1705	586	240	4875	50
480/70R38	145A8/145B	TL	R-1W	47.0	15.00	1683	483	160	2900	50
520/70R38	150A8/150B	TL	R-1W	48.0	16.00	1743	529	160	3350	50
580/70R38	155A8/155B	TL	R-1W	51.0	18.00	1822	580	160	3875	50
	170A8/170B	TL						280	6000	50
710/70R38	166A8/166B	TL	R-1W	58.0	23.00	1950	741	160	5300	50
*IF800/70R38	184B/184D	TL	R-1W	60.0	27.00	2085	805	240	9000	50
580/70R42	158A8/158B	TL	R-1W	51.0	18.00	1870	575	160	4250	50
	176A8/176B	TL						320	7100	50
620/70R42	160A8/160B	TL	R-1W	52.0	20.00	1917	626	160	4500	50
	166A8/166B	TL						240	5300	50
710/70R42	173A8/173B	TL	R-1W	58.0	23.00	2079	743	240	6500	50
	176A8/176B	TL						280	7100	50
710/75R42	175D/178A8	TL	R-1W	62.0	23.00	2127	728	240	7500	50

440/65R24	128D/131A8	TL	R-1W	45.0	14.00	1190	437	160	1800	65
480/65R24	133D/136A8	TL	R-1W	46.0	15.00	1224	469	160	2060	65
540/65R24	140D/143A8	TL	R-1W	48.0	16.00	1316	540	160	2500	65
440/65R28	131D/134A8	TL	R-1W	45.0	14.00	1288	439	160	1950	65
480/65R28	136D/139A8	TL	R-1W	46.0	15.00	1336	466	160	2240	65
540/65R28	142D/145A8	TL	R-1W	48.0	16.00	1424	533	160	2650	65
600/65R28	147D/150A8	TL	R-1W	49.0	18.00	1486	593	160	3075	65
	154D/157A8	TL						240	3750	65
540/65R30	143D/146A8	TL	R-1W	48.0	16.00	1477	535	160	2725	65
800/65R32	172A8/172B	TL	R-1W	57.0	25.00	1833	797	240	6300	40
	178A8/178B	TL						320	7500	40
IF800/65R32	181B/181D	TL	R-1W	57.0	28.00	1833	797	320	8250	65
*IF900/60R32	185B/185D	TL	R-1W	56.0	31.00	1910	891	320	9250	65
540/65R34	145D/148A8	TL	R-1W	48.0	16.00	1581	539	160	2900	65
600/65R34	151D/154A8	TL	R-1W	49.0	18.00	1665	607	160	3450	65
540/65R38	147D/150A8	TL	R-1W	48.0	16.00	1682	539	160	3075	65
600/65R38	153D/156A8	TL	R-1W	49.0	18.00	1768	604	160	3650	65
650/65R38	157D/160A8	TL	R-1W	51.0	20.00	1812	653	160	4125	65
	163D/166A8	TL						240	4875	65
650/65R42	158D/161A8	TL	R-1W	51.0	20.00	1921	651	160	4250	65
	165D/168A8	TL						240	5150	65

\*:With Steel Belt