

Technische Daten Tianli TUL300

Tyre Size	Load/Speed Index	Star Rating	TT/TL	TRA	Tread Depth	Rim	Outer Diameter	Section Width	Inflation Pressure	Load Capacity	Speed
					mm		mm	mm	KPa	Kg	Km/h
15.5R25	152B	★	TL	E-3	24. Apr	12.00/1.3	1275	405	375	3550	50
	169A2	★	TL	L-3					500	5800	10
17.5R25	167B	★★	TL	E-3	27.0	14.00/1.5	1347	449	525	5450	50
	182A2	★★	TL	L-3					650	8500	10
20.5R25	177B	★★	TL	E-3	31	17.00/2.0	1482	533	525	7300	50
	193A2	★★	TL	L-3					650	11500	10
	198A2	★★★★	TL	IND-3					800	13200	10
23.5R25	185B	★★	TL	E-3	41	19.5/2.5	1602	607	525	9250	50
	201A2	★★	TL	L-3					650	14500	10
	206A2	★★★★	TL	IND-3					800	17000	10
26.5R25	193B	★★	TL	E-3	38	22.00/3.0	1735	686	525	11500	50
	209A2	★★	TL	L-3					650	18500	10
	214A2	★★★★	TL	IND-3					800	21200	10
29.5R25	200B	★★	TL	E-3	45	25.00/3.5	1860	769	525	14000	50
	216A2	★★	TL	L-3					650	22400	10