

Technische Daten

Tianli SEWP

Tyre Size	P. R.	TT/TL	TRA	Tread Depth	Rim	Outer Diameter	Section Width	Inflation Pressure	Load Capacity	Speed
				mm		mm	mm	KPa	Kg	Km/h
18.04.1938	16	TT/TL	LS-1	41.0	W16A, DD16, W15L	1763	457	300	4375	30
*18.4-38	16	TT/TL	LS-1	41.0	W16A, DD16, W15L	1763	457	300	4375	30
16.09.1930	16	TT	LS-2	53.0	W15L, DW15A, W14L, DW14A	1488	414	310	3250	30
*16.9-30	16	TT	LS-2	53.0	W15L, DW15A, W14L, DW14A	1488	414	310	3250	30
18.04.2026	16	TT/TL	LS-2	50.5	DW16A	1450	455	280	3450	30
*18.4-26	16	TT/TL	LS-2	50.5	DW16A	1450	455	280	3450	30
18.04.1930	14	TL	LS-2	50.5	DW16A	1557	483	240	3350	30
	16	TT/TL						280	3650	30
*18.4-30	16	TT/TL	LS-2	50.5	DW16A	1557	483	280	3650	30
18.04.1934	14	TL	LS-2	51.0	DW16A, DW15A	1664	447	240	3550	30
	16	TT/TL						280	3875	30
*18.4-34	16	TT/TL	LS-2	51.0	DW16A, DW15A	1664	447	280	3875	30
20.05.2025	16	TL	LS-2	50.5	17.00/2.0 (1.7)	1450	427	225	4500	30
	20	TL						275	5000	30
20.08.1938	16	TT/TL	LS-2	50.5	W18A, DD18, DW18A	1834	528	250	4750	30
*20.8-38	16	TT/TL	LS-2	50.5	W18A, DD18, DW18A	1834	528	250	4750	30
23.01.2026	16	TT/TL	LS-2	63.5	DW20B	1628	584	240	4500	30
*23.1-26	16	TT/TL	LS-2	63.5	DW20B	1628	584	240	4500	30
	20	TT/TL						280	4875	30
24.05.1932	16	TT/TL	LS-2	59.5	DH21, DH21H	1806	587	210	5000	30
	20	TT						280	6000	30
*24.5-32	16	TT/TL	LS-2	59.5	DH21, DH21H	1806	587	210	5000	30
	20	TT/TL						280	6000	30
28L-26	24	TL	LS-2	57.0	DW25B	1676	683	340	6700	30
	16	TT						210	4750	30
30.5L-32	18	TT	LS-2	57.0	DW25B	1676	683	220	4875	30
	16	TT/TL						170	5300	30
*30.5L-32	20	TT/TL	LS-2	66.5	DH27, DH27H	1844	732	210	6000	30
	16	TT						170	5300	30
*30.5L-32	20	TT/TL	LS-2	66.5	DH27, DH27H	1844	732	210	6000	30
	26	TT						280	15700	30
*380/85-24	14	TL	LS-2	47.5	W12	1260	380	240	2300	40
*380/85-28	14	TL	LS-2	47.5	W12	1365	380	240	2430	40
*420/85-28	14	TL	LS-2	53.5	W15L, W14L	1432	428	240	2800	40

*:With Steel Belt