

## Technische Daten

## SLG II SUPER LOADER GRADER II

Tyre Size	P. R.	TT/TL	TRA	Tread Depth	Rim	Outer Diameter	Section Width	Inflation Pressure	Load Capacity	Speed
				mm		mm	mm	KPa	Kg	Km/h
13.00-24	12	TT/TL	G-2	24.0	10.00VA	1285	353	300	2725	40
	16	TL						375	3250	40
14.00-24	12	TT/TL	G-2	25.5	10.00VA	1354	381	250	3075	40
	16	TT/TL						350	3650	40
16.00-24	16	TL	G-2	30.5	10.00VA	1491	455	300	4500	40
10.5/80-18	10	TL	L-2	20.0	9×18	904	269	375	1950	40
	12	TL						450	2150	40
12.5/80-18	12	TL	L-2	22.0	11×18	991	325	350	2240	40
10.5-20	12	TL	L-2	26.0	9×20	955	269	425	2240	40
12.5-20	12	TL	L-2	23.0	11×20	1039	325	350	2300	40
21.00-28	24	TT/TL	L-2	40.0	15.00-28/3.0	1790	570	350	8850	40
	12	TL						400	5600	10
15.5-25	16	TL	L-2	25.0	12.00/1.3	1272	394	250	2650	40
								550	6750	10
	12	TT/TL	350	3225	40					
17.5-25	12	TT/TL	L-2	25.5	14.00/1.5	1344	450	350	6150	10
								200	2900	40
	475	7300						10		
	275	3350						40		
	575	8250						10		
20	TT/TL	325	3650	40						
20.5-25	12	TL	L-2	28.5	17.00/2.0	1460	493	250	6700	10
								175	3550	40
	350	8250						10		
	225	4000						40		
	450	9500						10		
16	TT/TL	275	4500	40						
23.5-25	16	TT/TL	L-2	31.5	19.50/2.5	1600	592	300	9500	10
								200	4750	40
	20	TT/TL						375	10900	10
14.9-24	8	TT	R-4	25.0	W12、W13	1241	378	210	2300	40
	12	TL						290	2900	40
16.9-24	10	TL	R-4	24.0	W15L	1290	396	220	2900	40
	12	TT/TL						260	3250	40
16.9-28	12	TL	R-4	25.5	W14L、W15L	1359	396	260	3450	40
18.4-24	10	TT/TL	R-4	25.5	W15L、W16L	1359	450	210	3350	40
	12	TL						250	3750	40
18.4-26	10	TL	R-4	25.0	DW16A、W15L	1372	457	210	3550	40
	12	TT/TL						250	4000	40
	16	TL						330	4800	40
17.5L-24	8	TL	R-4	25.0	W15L	1240	445	180	2430	40
	12	TL						260	3125	40
	10	TL						190	3000	40
19.5L-24	12	TL	R-4	25.0	W15L、W16L、DW16A	1314	495	230	3450	40
	14	TL						DW16A	275	3830
21L-24	12	TL	R-4	29.0	DW18A	1378	533	220	3875	40
	16	TL						280	4500	40