

## Technische Daten

## Marcher Forestry LS-2

Tyre Size	P. R.	TT/TL	Rim	Tread Depth	Outer Diameter	Section Width	Inflation Pressure	Load Capacity
				mm	mm	mm	KPa	Kg
16.9-30	10	TT/TL	W15L	48	1510	210	210	2575
	16	TT/TL	W15L	48	1510	210	300	3210
18.4-26	10	TT/TL	DW16A	50	1475	465	170	2575
	16	TT/TL	DW16A	50	1475	465	280	3500
18.4-30	10	TT/TL	DW16A	50	1575	465	170	2725
	16	TT/TL	DW16A	50	1575	465	280	3600
18.4-34	12	TT/TL	DW16A	50	1680	465	210	3250
	16	TT/TL	DW16A	50	1680	465	280	3700
23.1-26	14	TT/TL	DW20A	53	1630	590	210	4125
	16	TT/TL	DW20A	53	1630	590	240	4450
24.5-32	16	TT/TL	DH21	55	1830	625	210	5000
	20	TT/TL	DH21	55	1830	625	280	5800
28L-26	18	TT/TL	DW25A	55	1645	715	210	4800
	20	TT/TL	DW25A	55	1645	715	240	5150
30.5L-32	18	TT/TL	DH27	55	1845	775	210	5950
	20	TT/TL	DH27	55	1845	775	240	6530
	26	TT/TL	DH27	55	1845	775	280	7100
DH35.5L-32	20	TT/TL	DH32	58	2004	905	240	6530
	26	TT/TL	DH32	58	2004	905	280	8750
73x44.00-32	16	TL	DH36	67	1870	1153	280	6900
	20	TL	DH36	67	1870	1153	340	8000