

Technische Daten

Tianli FG Forest Grip

| Tyre Size | P. R. | TT/TL | TRA | Tread Depth | Rim | Outer Diameter | Section Width | Inflation Pressure | Load Capacity | Speed |
|--------------|------------|-------|------|-------------|------------|----------------|---------------|--------------------|---------------|-------|
| | | | | mm | | mm | mm | KPa | Kg | Km/h |
| 23.01.2026 | 16 | TT | LS-2 | 53.5 | DW20B | 1632 | 587 | 240 | 4500 | 30 |
| *23.1-26 | 16 | TT/TL | LS-2 | 53.5 | DW20B | 1632 | 587 | 240 | 4500 | 30 |
| 28L-26 | 20 | TT | LS-2 | 57.0 | DW25B | 1644 | 714 | 240 | 5150 | 30 |
| *28L-26 | 20 | TT/TL | LS-2 | 57.0 | DW25B | 1644 | 714 | 240 | 5150 | 30 |
| 30.5L-32 | 20 | TT/TL | LS-2 | 56.0 | DH27、DH27H | 1847 | 775 | 210 | 6000 | 30 |
| *30.5L-32 | 20 | TT/TL | LS-2 | 56.0 | DH27、DH27H | 1847 | 775 | 210 | 6000 | 30 |
| | 26 | TL | | | | | | 280 | 15700 | 30 |
| *500/60-26.5 | 16 | TL | LS-2 | 53.5 | 16.00 | 1265 | 485 | 450 | 4875 | 40 |
| | 20 | TL | | | | | | 500 | 5600 | 40 |
| *600/50-22.5 | 16 | TT/TL | LS-2 | 42.0 | 20.00 | 1151 | 601 | 320 | 3250 | 40 |
| | 20 | TT/TL | | | | | | 500 | 4375 | 40 |
| | 24 | TL | | | | | | 600 | 6500 | 40 |
| *600/55-26.5 | 16 | TL | LS-2 | 53.5 | 20.00 | 1333 | 601 | 400 | 4500 | 40 |
| | 20 | TT/TL | | | | | | 500 | 5150 | 40 |
| *600/60-30.5 | 20 | TL | LS-2 | 45.0 | 20.00 | 1511 | 607 | 400 | 5600 | 40 |
| *650/45-22.5 | 16 | TL | LS-2 | 45.0 | 20.00 | 1153 | 635 | 320 | 3350 | 40 |
| | 20 | TL | | | | | | 400 | 3750 | 40 |
| | 24 | TL | | | | | | 600 | 6900 | 40 |
| *710/40-22.5 | 16 | TT/TL | LS-2 | 42.0 | 24.00 | 1151 | 700 | 360 | 3750 | 40 |
| | 20 | TT/TL | | | | | | 500 | 4625 | 40 |
| | 24 | TL | | | | | | 550 | 6500 | 40 |
| *710/40-24.5 | 20 | TT/TL | LS-2 | 48.0 | 24.00 | 1230 | 700 | 500 | 4875 | 40 |
| *710/45-26.5 | 16 | TL | LS-2 | 53.0 | 24.00 | 1333 | 700 | 400 | 4875 | 40 |
| | 20 | TT/TL | | | | | | 500 | 5600 | 40 |
| *780/50-28.5 | 24 | TL | LS-2 | 39.0 | 26.00 | 1528 | 793 | 600 | 8500 | 40 |
| *800/35-22.5 | 20 | TL | LS-2 | 42.0 | 28.00 | 1140 | 800 | 400 | 4000 | 40 |
| *800/40-26.5 | 20 | TT/TL | LS-2 | 53.5 | 28.00 | 1333 | 811 | 500 | 6000 | 40 |
| *710/45R26.5 | 168A8/175A | TL | LS-2 | 53.0 | 24.00 | 1333 | 700 | 500 | 5600 | 40 |

*:With Steel Belt