

Technische Daten

Tianli SL Super Logger

Tyre Size	P. R.	TT/TL	TRA	Tread Depth	Rim	Outer Diameter	Section Width	Inflation Pressure	Load Capacity	Speed
				mm		mm	mm	KPa	Kg	Km/h
23.1-26	16	TT	LS-2	53.5	DW20B	1632	587	240	4500	30
*23.1-26	16	TT/TL	LS-2	53.5	DW20B	1632	587	240	4500	30
23.1-34	16	TT/TL	LS-2	53.5	DW20B	1835	587	240	5000	30
*23.1-34	16	TT	LS-2	53.5	DW20B	1835	587	240	5000	30
24.5-32	16	TT	LS-2	54.5	DH21、DH21H	1831	622	210	5000	30
*24.5-32	16	TT	LS-2	54.5	DH21、DH21H	1831	622	210	5000	30
	20	TT/TL						280	6000	30
28L-26	16	TT	LS-2	57.0	DW25B	1644	714	210	4750	30
	20	TT						240	5150	30
*28L-26	16	TT	LS-2	57.0	DW25B	1644	714	210	4750	30
	20	TT/TL						240	5150	30
30.5L-32	20	TT/TL	LS-2	62.5	DH27、DH27H	1868	775	210	6000	30
	26	TT/TL						280	7100	30
*30.5L-32	20	TT/TL	LS-2	62.5	DH27、DH27H	1868	775	210	6000	30
	26	TL						280	7100	30
DH35.5L-32	20	TT/TL	LS-2	63.5	DH31、DH31H	1935	878	170	7300	30
	26	TL						240	8750	30
*DH35.5L-32	20	TT/TL	LS-2	63.5	DH31、DH31H	1935	878	170	7300	30
	26	TL						240	8750	30
*700/70-34	16	TT/TL	LS-2	50.0	DW20B	1844	700	240	5600	40
	20	TL						320	6500	40
	24	TL						400	7500	40

*:With Steel Belt