

Technische Daten

Tianli FF

Tyre Size	P. R.	TT/TL	TRA	Tread Depth	Rim	Outer Diameter	Section Width	Inflation Pressure	Load Capacity	Speed
				mm		mm	mm	KPa	Kg	Km/h
*22/65-25	16	TT/TL	HF-2/LS-1	24.0	17.00/1.7(2.0)	1362	555	325	5300	30
*500/60-22.5	16	TT/TL	HF-2/LS-1	35.0	16.00	1171	503	320	3450	40
	20	TL						360	3750	40
*600/50-22.5	16	TT/TL	HF-2/LS-1	35.0	20.00	1171	601	320	3250	40
600/55-26.5	16	TL	HF-2/LS-1	40.0	20.00	1344	610	400	4500	40
*600/55-26.5	16	TL	HF-2/LS-1	40.0	20.00	1344	610	400	4500	40
	20	TT/TL						500	5150	40
600/60-30.5	16	TL	HF-2/LS-1	40.0	20.00	1500	600	320	4875	40
	20	TL						400	5600	40
*600/60-30.5	16	TT/TL	HF-2/LS-1	40.0	20.00	1500	600	320	4875	40
	20	TT/TL						400	5600	40
*650/65-26.5	20	TT/TL	HF-2/LS-1	35.0	20.00	1476	658	500	6700	40
*700/50-30.5	16	TL	HF-2/LS-1	40.0	24.00	1500	700	280	5000	40
	20	TT/TL						370	5800	40
*710/40-22.5	16	TT/TL	HF-2/LS-1	35.0	24.00	1171	700	360	3750	40
*710/45-26.5	20	TT/TL	HF-2/LS-1	40.0	24.00	1344	710	500	5600	40
	24	TL						600	6500	40
*750/55-26.5	16	TT/TL	HF-2/LS-1	35.0	24.00	1476	758	400	6300	40
	20	TT/TL						500	7300	40
*800/40-26.5	16	TL	HF-2/LS-1	40.0	28.00	1344	810	400	5000	40
	20	TT/TL						500	6000	40
800/45-30.5	20	TL	HF-2/LS-1	40.0	28.00	1500	800	350	6700	40
*800/45-30.5	16	TL	HF-2/LS-1	40.0	28.00	1500	800	280	5800	40
	20	TT/TL						350	6700	40

*:With Steel Belt