

## Technische Daten Agro Grip

Tyre Size	Load Speed Index	TT/TL	TRA	Tread Depth	Rim	Outer Diameter	Section Width	Inflation Pressure	Load Capacity	Speed
				mm		mm		KPa	Kg	Km/h
500/50R17	149D	TL	-	15.0	16.00	932	503	450	3250	65
500/60R22 .5	155D	TL	-	25.0	16.00	1170	506	400	3875	65
560/45R22 .5	152D	TL	-	25.0	16.00	1072	538	400	3550	65
560/60R22 .5	161D	TL	-	25.0	16.00	1256	562	400	4625	65
*560/60R2 2.5	164D	TL	-	25.0				400	5000	65
600/50R22 .5	159D	TL	-	25.0	20.00	1168	608	400	4375	65
*600/50R2 2.5	167D	TL	-	25.0				500	5450	65
600/55R22 .5	162D	TL	-	25.0	20.00	1214	610	400	4750	65
650/50R22 .5	163D	TL	-	25.0	20.00	1208	654	400	4875	65
710/45R22 .5	165D	TL	-	25.0	24.00	1202	718	400	5150	65
*710/45R2 2.5	165D	TL	-	25.0	24.00	1202	718	400	5150	65
600/55R26 .5	165D	TL	-	25.0	20.00	1320	610	400	5150	65
620/55R26 .5	166D	TL	-	25.0	20.00	1378	641	400	5300	65
650/55R26 .5	169D	TL	-	25.0	20.00	1396	650	400	5800	65
*650/55R2 6.5	178D	TL	-	25.0	20.00	1396	650	500	7500	65
*710/50R2 6.5	170D	TL	-	25.0	24.00	1368	728	400	6000	65
750/45R26 .5	170D	TL	-	25.0	24.00	1345	751	400	6000	65
*600/60R3 0.5	169D	TL	-	25.0	20.00	1487	624	400	5800	65
	173D	TL						400	6500	65
	179D	TL						500	7750	65
*650/65R3 0.5	176D	TL	-	25.0	20.00	1620	650	400	7100	65
*710/50R3 0.5	176D	TL	-	25.0	24.00	1470	719	400	7100	65
*750/60R3 0.5	181D	TL	-	25.0	24.00	1658	767	400	8250	65
*850/50R3 0.5	182D	TL	-	25.0	28.00	1610	862	400	8500	65

\*:With Steel Belt