



WLB 550

Product Data Sheet

Marketing Department.
December 28 , 2020

This document is created to register the marketing communication collaterals and process details for the launch of the above-mentioned pattern; it is intended for internal circulation and approval for further dissemination. All facts and figures mentioned in the document is true to the best of our knowledge as on the above said date, for updated information please feel free to visit the website www.ascensotyres.com

Release Month: December'20

Brand: ASCENSO

Tread Pattern : WLB 550

Tyre Construction: Bias

Type: Tube Less

Main Applications: Wheel Loader

TRA Code : L-3

List of Sizes

Size	PR
17.5-25	16,20,24
20.5-25	16
20.5-25	20
23.5-25	20



Salient Features

Robust Tread Design:

Generates maximum traction & resistance to slippage

Strong Nylon Casing:

- High load carrying capacity
- Resistance to impacts



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Infl. Pressure	Recommend load, kg (lbs)		
		SW	OD					Speed, km/h(mph)		
		mm	mm				mm	mm	Bar	10
		In	in				in	in	Psi	7
17.5-25	14.00/15	445 17.5	1348 53.1	612 24.1	4032 158.7	16 PR 177 A2	4.75	7300		
							69	16060		
						20 PR 181 A2	5.75	8250		
							84	18150		
						24 PR 188 A2	7	10000		
							102	22000		
20.5-25	17.00/2.0	520 20.5	1492 58.7	672 26.4	4463 175.7	16 PR 181 A2	3.5	8250		
							51	18150		
						20 PR 186 A2	4.5	9500		
							66	20900		
23.5-25	19.5/1.5	597 23.5	1617 63.7	723 28.5	4837 190.4	20 PR 191 A2	3.75	10900		
							55	23980		

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover