



TSB 112

New Product Release Document

Marketing Department.

July 08, 2022

This document is created to register the marketing communication collaterals and process details for the launch of the above-mentioned pattern; it is intended for internal circulation and approval for further dissemination. All facts and figures mentioned in the document is true to the best of our knowledge as on the above said date, for updated information please feel free to visit the website www.ascensotyres.com

New Product Release Document

ReleaseMonth: July'22

Brand: ASCENSO

Tread Pattern : TSB 112

Tyre Construction: Bias

Type: Tube Less

Main Applications: 2WD Tractors

TRA Code : F2

List of Sizes

Size	LSI
9.5L-15 SL	8
11L-15 SL	8
10.00-16 SL	8
11.00-16 SL	8



Salient Features

Wider Centre Rib:

- Provides Ease in steering.
- Better Manoeuvring

High Strength Nylon Carcass

- Provides longer tyre life
- Trouble free service.



Technical Specification

Size	Rim	Unloaded Dimension		Static Load Radius	Rolling Circumference	Load Index / Speed Index	Inflation Pressure	Recommended load, kg (lbs)					
		Speed, km/h (mph)											
		Mixed application											
		bar	Static					15	25	30	40		
psi	9			15	20	25							
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
in	in	in	in	in	in	in	in	in	in	in	in	in	in
9.5L-15SL	8LB	251 9.88	782 30.79	356 14.02	2339 92.09	8PR 102 A8	2.5	1440	1080	920	800	720	
							36	3170	2380	2030	1760	1590	
							2.7	1500	1130	960	830	750	
							39	3300	2490	2110	1830	1650	
							3.0	1600	1200	1020	890	800	
							44	3520	2640	2250	1960	1760	
							3.3	1700	1280	1090	940	850	
							48	3740	2820	2400	2070	1870	
11L-15SL	8LB	279 10.98	813 32.01	369 14.53	2432 95.75	8PR 106 A8	2.3	1620	1220	1040	900	810	
							33	3570	2690	2290	1980	1780	
							2.5	1700	1280	1090	940	850	
							36	3740	2820	2400	2070	1870	
							2.7	1780	1340	1140	990	890	
							39	3920	2950	2510	2180	1960	
							3	1900	1430	1220	1050	950	
							44	4190	3150	2690	2310	2090	

Note:All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6th Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: www.ascensotyres.com

Technical Specification

Size	Rim	Unloaded Dimension		Static Load Radius	Rolling Circumference	Load Index / Speed Index	Inflation Pressure	Recommended load, kg (lbs)				
		SW	OD					Speed, km/h (mph)				
								Mixed application				
		mm	mm					Static	15	25	30	40
in	in	9	15	20	25							
10.00-16SL	8LB	274 10.79	894 35.20	404 15.91	2674 105.28	8PR 110 A8	2.3	1820	1370	1160	1010	910
							33	4010	3020	2560	2220	2000
							2.5	1920	1440	1230	1070	960
							36	4230	3170	2710	2360	2110
							2.7	2000	1500	1280	1110	1000
							39	4410	3300	2820	2440	2200
							3	2120	1590	1360	1180	1060
							44	4670	3500	3000	2600	2330
11.00-16SL	10LB	315 12.40	967 38.07	434 17.09	2892 113.86	8PR 114 A8	2.2	2060	1550	1320	1140	1030
							32	4540	3410	2910	2510	2270
							2.4	2160	1620	1380	1200	1080
							35	4760	3570	3040	2640	2380
							2.6	2260	1700	1450	1250	1130
							38	4980	3740	3190	2750	2490
							2.8	2360	1770	1510	1310	1180
							41	5200	3900	3330	2890	2600

Note: All tyres conform to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6th Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: www.ascensotyres.com