

# Technische Daten Tianli R100

Tyre Size	Load Speed Index/P. R.	TT/TL	TRA	Tread Depth	Rim	Outer Diameter	Section Width	Inflation Pressure	Load Capacity	Speed
				mm		mm	mm	KPa	Kg	Km/h
10.0/75-15.3	10	TL	-	23.0	9.00	790	270	390	1395 (Free Rolling) 980 (Drive Wheel)	50
11.5/80-15.3	12	TL	-	23.0	9.00	870	300	410	1960 (Free Rolling) 1395 (Drive Wheel)	50
15.0/55-17	14	TL	-	23.0	13.00	872	388	360	2320 (Free Rolling) 1665 (Drive Wheel)	50
19.0/45-17	10	TL	-	25.0	16.00	865	465	220	2120 (Free Rolling) 1485 (Drive Wheel)	50
	16	TL						300	2700 (Free Rolling) 1850 (Drive Wheel)	50
DW500/95D 32	12	TL	-	50.0	DW13	1812	506	172	4420 (Drive Wheel)	50
31×15.50R15	122B	TL	-	19.0	13LB	792	391	280	1500	50
425/55R17	134D	TL	-	27.0	13.00	881	425	350	2120	65
500/50R17	145D	TL	-	25.0	16.00	920	499	400	2900	65