

Technische Daten Tianli BRS

Tyre Size	Load Speed Index	TT/TL	TRA	Tread Depth	Rim	Outer Diameter	Section Width	Inflation Pressure	Load Capacity	Speed
				mm		mm	mm	KPa	Kg	Km/h
280/80R18	132A8/132 B	TL	R-4	28.0	9.00	914	288	400	2000	50
340/80R18	143A8/143 B	TL	R-4	30.0	11.00	996	353	400	2725	50
400/70R18	147A8/147 B	TL	R-4	33.0	13.00	1020	408	400	3075	50
280/80R20	133A8/133 B	TL	R-4	28.0	9.00	967	285	400	2060	50
340/80R20	144A8/144 B	TL	R-4	30.0	11.00	1053	356	400	2800	50
380/75R20	148A8/148 B	TL	R-4	33.0	12.00	1088	386	400	3150	50
*400/70R20	149A8/149 B	TL	R-4	33.0	13.00	1072	408	400	3250	50
400/70R24	152A8/152 B	TL	R-4	33.0	13.00	1172	407	400	3550	50
440/80R24	161A8/161 B	TL	R-4	36.0	14.00	1312	457	400	4625	50
460/70R24	159A8/159 B	TL	R-4	36.0	15.00	1247	468	400	4375	50
500/70R24	164A8/164 B	TL	R-4	36.0	16.00	1317	505	400	5000	50
480/80R26	160A8/160 B	TL	R-4	36.0	15.00	1412	497	320	4500	50
440/80R28	156A8/156 B	TL	R-4	36.0	14.00	1416	456	320	4000	50
	163A8/163 B	TL						400	4875	50

*:With Steel Belt